

Gross rear axle (kg)

NISSAN NAVARA

Specifications	Single Cab RX CC 4x4 Diesel	King Cab RX CC 4x4 Diesel	King Cab ST-X CC 4x4 Diesel	King Cab ST-X PU 4x4 Diesel	Dual Cab RX PU 4x2 Diesel	Dual Cab RX PU 4x4 Diesel	Dual Cab RX CC 4x4 Diesel	Dual Cab ST PU 4x2 Diesel	Dual Cab ST PU 4x4 Diesel	Dual Cab ST-X PU 4x4 Diesel	Dual Cab ST-X 550 4x4 Diesel
Engine											
2.5 litre intercooled turbo-diesel, DOHC	•	•	•	•	•	•	•	•	•		
3.0 litre V6 intercooled turbo-diesel, DOHC										•	•
Displacement (cc)	2488	2488	2488	2488	2488	2488	2488	2488	2488	2993	2993
Bore x stroke (mm)	89x100	89x100	89x100	89x100	89x100	89x100	89x100	89x100	89x100	84x90	84x90
Max power (kW@rpm)	106@4000	126@4000	126@4000	126@4000	106@4000	126@4000	126@4000	120@4000	140@4000	170@3750	170@3750
Max torque (Nm@rpm)	356@2000	403@2000	403@2000	403@2000	356@2000	403@2000	403@2000	403@2000	450@2000	550@1750	550@1750
Transmission				I	ı						I
6-speed manual	•	•	•	•	•	•	•	•	•		
5-speed automatic		Opt	Opt	Opt	Opt	Opt	Opt				
5-speed automatic with manual mode								Opt	Opt		
7-speed automatic with manual mode										•	•
Transfer case - Dual range 4x4 with electric 4WD selection	•	•	•	•		•	•		•	•	•
Ratio 1st manual	4.692	4.692	4.692	4.692	4.692	4.692	4.692	4.692	4.692		
Ratio 2nd manual	2.705	2.705	2.705	2.705	2.705	2.705	2.705	2.705	2.705		
Ratio 3rd manual	1.747	1.747	1.747	1.747	1.747	1.747	1.747	1.747	1.747		
Ratio 4th manual	1.291	1.291	1.291	1.291	1.291	1.291	1.291	1.291	1.291		
Ratio 5th manual	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000		
Ratio 6th manual	0.827	0.827	0.827	0.827	0.827	0.827	0.827	0.827	0.827		
Ratio reverse manual	4.260	4.260	4.260	4.260	4.260	4.260	4.260	4.260	4.260		
Final drive manual	3.538	3.692	3.692	3.692	3.538	3.692	3.692	3.538	3.692		
Ratio 1st automatic		3.827	3.827	3.827	3.827	3.827	3.827	3.827	3.827	4.886	4.886
Ratio 2nd automatic		2.368	2.368	2.368	2.368	2.368	2.368	2.368	2.368	3.169	3.169
Ratio 3rd automatic		1.519	1.519	1.519	1.519	1.519	1.519	1.520	1.520	2.027	2.027
Ratio 4th automatic		1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.411	1.411
Ratio 5th automatic		0.834	0.834	0.834	0.834	0.834	0.834	0.834	0.834	1.000	1.000
Ratio 6th automatic										0.864	0.864
Ratio 7th automatic										0.774	0.774
Ratio reverse automatic		2.613	2.613	2.613	2.613	2.613	2.613	2.613	2.613	4.041	4.041
Final drive automatic		3.538	3.538	3.538	3.538	3.538	3.357	3.357	3.538	3.133	3.133
Transfer ratio - low	2.625	2.625	2.625	2.625		2.625	2.625		2.625	2.625	2.625
Transfer ratio - high	1.000	1.000	1.000	1.000		1.000	1.000		1.000	1.000	1.000
Dimensions											
Overall length (mm)	5140	5125	5125	5230	5125	5125	5125	5296	5296	5296	5296
Overall width (excluding mirrors) (mm)	1795	1850	1850	1850	1850	1850	1850	1848	1848	1848	1848
Overall height (w/o roof rail) (mm)	1740	1770	1770	1770	1780	1780	1780	1788	1795	1795	1795
Wheelbase (mm)	3200	3200	3200	3200	3200	3200	3200	3200	3200	3200	3200
Track front/rear (mm)	1550/1550	1570/1570	1570/1570	1570/1570	1570/1570	1570/1570	1570/1570	1570/1570	1570/1570	1570/1570	1570/1570
Minimum. turning circle kerb to kerb (m)	12.5	13.2	13.2	13.2	13.2	13.2	13.2	13.4	13.3	13.3	13.3
Tare mass incl options (kg)# manual/automatic	1637#	1753/1783#	1787/1817#	1957/1987	1884/1899	1989/2005	1849/1865#	1878/1893	1937/1977	2060	2104
Gross Vehicle Mass (GVM**) (kg)	2860	2860	2860	2860	2860	2860	2860	2805	2805	3010	3010
Carrying capacity (kg) manual/automatic	1223∆(manual)	1107/1077∆	1073/1043⁴	903/873	976/961	871/855	1011/995∆	927/912	868/828	950 (automatic only)	906 (automatic only
Ground clearance unladen (mm)	190	205	205	205	205	205	205	227	228	228	228
Overhang - front	800	800	800	800	800	800	800	866	866	866	866
Overhang - rear	1140	1125	1125	1230	1230	1125	1125	1230	1230	1230	1230
Angle of approach	32.0	32.0	32.0	32.0	32.0	32.0	32.0	30.0	30.0	30.0	30.0
Angle of departure	27.5	27.5	27.5	24.0	27.5	27.5	27.5	24.0	24.0	24.0	24.0
Tray length floor (mm)				1865	1513	1513		1511	1511	1511	1511
Tray length top (mm)				1830	1480	1480		1487	1487	1487	1487
Tray width floor (mm)				1560	1550	1550		1560	1560	1560	1560
Tray width top (mm)				1495	1494	1494		1496	1496	1496	1496
Tray width between wheel arches (mm)				1135	1134	1134		1130	1130	1130	1130
Tray width tailgate opening width				1435	1435	1435		1432	1432	1432	1432
Tray height (mm)				454	454	454		457	457	457	457
Rated Towing Capacity [†]											
Trailer with brakes (kg)	3000	3000	3000	3000	2000	3000	3000	2000	3000	3000	3000
Trailer without brakes (kg)	750	750	750	750	750	750	750	750	750	750	750
Towball download (kg)	See Table	See Table	See Table	See Table	See Table	See Table	See Table	See Table	See Table	See Table	See Table
Gross front axle (kg)	1365	1365	1365	1365	1365	1365	1365	1365	1365	1530	1530
Gross rear axle (kn)	1720	1720	1720	1720	1720	1720	1720	1720	1720	1717	1717



NISSAN NAVARA

Specifications Fuel	Single Cab RX CC 4x4 Diesel	King Cab RX CC 4x4 Diesel	King Cab ST-X CC 4x4 Diesel	King Cab ST-X PU 4x4 Diesel	Dual Cab RX PU 4x2 Diesel	Dual Cab RX PU 4x4 Diesel	Dual Cab RX CC 4x4 Diesel	Dual Cab ST PU 4x2 Diesel	Dual Cab ST PU 4x4 Diesel	Dual Cab ST-X PU 4x4 Diesel	Dual Cab ST-X 550 4x4 Diesel
Fuel type - diesel	•	•	•	•	•	•	•	•	•	•	•
Fuel tank capacity (litres)	80	80	80	80	80	80	80	80	80	80	80
Fuel consumption I/100km (combined ADR 81/02) [®] (manual)	9.3	9.8	9.8	9.8	9.1	9.8	9.8	8.3	8.5	00	00
Fuel consumption I/100km (combined ADR 81/02) [®] (automatic)	0.0	10.5	10.5	10.5	9.9	10.5	10.5	8.7	9.0	9.3	9.3
ruei consumption i/ Tookin (comoineu ADK 61702)* (automatic)		10.0	10.0	10.0	9.8	10.0	10.0	0.1	3.0	უ.ა	შ.ა
Mechanical											
Front brakes - ventilated discs	•	•	•	•	•	•	•	•	•	•	•
Rear brakes - drum	•	•	•	•	•	•	•	•	•	•	•
Front suspension - independent double wishbone with coil over shock	•	•	•	•	•	•	•	•	•	•	•
Rear suspension - rigid axle with leaf spring	•	•	•	•	•	•	•	•	•	•	•
Rack and pinion power assisted steering	•	•	•	•	•	•	•	•	•	•	•
Mechanical limited slip differential	•	•	•	•	•	•	•	•			
Wheels/Tyres											
16x6 J steel wheels with 205/R16C tyres	•										
16x7 J steel wheels with 255/70R16 tyres		•			•	•	•				
16x7 J alloy wheels with 255/70R16 tyres			•	•							
17x7 J alloy wheels with 255/65R17 tyres								•	•	•	•
Spare Steel Wheel	•	•	•	•	•	•	•	•	•	•	•
Interior Seating capacity	2	4	4	4	5	5	5	5	5	5	5
Drivers seat height adjust						J				•	•
8-way power adjustable drivers seat											•
Electric slide and recline front passenger seat											•
Seat trim	Cloth	Cloth	Cloth	Cloth	Cloth	Cloth	Cloth	Cloth	Cloth	Cloth	Leather accented*
Front heated seats	GIUIII	GIULII	GIUIII	GIUIII	GIULII	GIUIII	GIUIII	GIULII	GIUIII	GIULII	LEGUIEI GUUGIILGU
60/40 split fold rear bench seat								•	•	•	•
Flip up rear seats		•	•	•				•	•	•	•
Fold down rear seats					•	•	•	•	•	•	•
Air-conditioning with rotary type heater controls	•	•	•	•	•	•	•	•	-		-
Air-conditioning with rotary type neater control								•	•	•	•
External temperature display								•	•	•	•
Power windows	•	•	•	•	•	•	•	•	•	•	•
Remote central locking	•	•	•	•	•	•	•	•	•	•	•
Tilt adjustable steering	•	•	•	•	•	•	•	•	•	•	•
Single CD player with AM/FM radio	•	•	•	•	•	•	•	•	•	•	•
Steering wheel audio controls	•	•	•	•	•	•	•	•	•	•	•
Audio system with Bose® speakers		_									•
Audio unit - speed sensing volume								•	•	•	•
Speakers	2	2	4	4	4	4	4	6	6	6	6 & subwoofer
Bluetooth® handsfree phone system via steering wheel controls		•	•	•	•	•	•	•		•	o & subwooler
Auxiliary MP3 player input jack	•	•	•	•	•	•	•	•	•	•	•
iPod^ connectivity via USB connection								•	•	•	•
HDD Satellite Navigation with 3D mapping and 7" integrated colour display with touch screen and steering wheel controls											•
DVD player from front colour display											•
9.3GB Music Box Hard Drive											•
Removable rear under seat storage with net cover										•	•
Cruise control	•	•	•	•	•	•	•	•	•	•	•
Sunglasses holder (overhead console)								•	•	•	•
Leather accented steering wheel and leather accented shift lever*								•	•	•	•
Floor carpet			•	•				•	•	•	•
Custom red trimmed floor mats											•
Vinyl floor coverings	•	•			•	•	•				
12 volt power socket	•	•	•	•	•	•	•	•	•	•	•
Door pockets	•	•	•	•	•	•	•	•	•	•	•
Front seat back pocket(s)	•	•	•	•	•	•	•	Driver Only	Driver Only	Driver Only	Driver Only
	•	•	•	•	•	•	•	Dilver unity	Driver unity	Diliver utiliy	Diliver utily
Upper and lockable lower glovebox	•	•	•			•	•	•	•	•	•
Centre console with lid				•	•						
Centre dashboard storage tray	•	•	•	•	•	•	•	•	•	•	•
Door drink/bottle holders	•	•	•	•	•	•	•	•	•	•	•
Front cup holder - in centre console Rear cup holder - in centre console	•	•	•	•	•	•	•	•	•	•	•
		•	•	•		•				1	1



Chrome frame grille Lockable fuel lid

NISSAN NAVARA

	Single Cab	King Cab	King Cab	King Cab	Dual Cab	Dual Cab	Dual Cab	Dual Cab	Dual Cab	Dual Cab	Dual Cab
Specifications	RX CC 4x4 Diesel	RX CC 4x4 Diesel	ST-X CC 4x4 Diesel	ST-X PU 4x4 Diesel	RX PU 4x2 Diesel	RX PU 4x4 Diesel	RX CC 4x4 Diesel	ST PU 4x2 Diesel	ST PU 4x4 Diesel	ST-X PU 4x4 Diesel	ST-X 550 4x4 Diesel
Illuminated ignition switch	TAT DIGGGI	•	•	•	• • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • •	•	• • • • • • • • • • • • • • • • • • •	•	•	
Assist grip(s)	•	•	•	•	•	•	•	•	•	•	•
Door operated courtesy lights	•	•	•	•	•	•	•	•	•	•	•
Map lights					•	•	•	•	•	•	•
Drivers foot rest	•	•	•	•	•	•	•	•	•	•	•
Rear heater vents								•	•	•	•
Key ring											•
						,					
Instrumentation			T	I	ı	I		I	1		
Drive computer (distance to empty, average fuel economy, fuel economy record, elapsed time, drive distance, average speed and maintainance information)										•	•
Drive computer (distance to empty, average speed, average fuel consumption, journey time)								•	•		
Odometer, tachometer and dual trip meters	•	•	•	•	•	•	•	•	•	•	•
Digital clock	•	•	•	•	•	•	•	•	•	•	•
4WD indicator	•	•	•	•		•	•		•	•	•
Distance to next service	•	•	•	•	•	•	•	•	•	•	•
Low fuel warning light	•	•	•	•	•	•	•	•	•	•	•
Automatic transmission indicator in dash	-	Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt	•	•
Automatic transmission mulcator in dash Automatic transmission shift interlock			· ·		Opt	Opt			-	•	•
		Opt	Opt	Opt	Upt		Opt	Opt	Opt		•
Headlights on - audible warning	•	•	•	•	•	•	•	•	•	•	•
Safety											
Engine immobiliser	•	•	•	•	•	•	•	•	•	•	•
Driver and front passenger front-impact SRS airbags	•	•	•	•	•	•	•	•	•	•	•
Driver and front passenger side-impact SRS airbags								•	•	•	•
Front to rear SRS curtain airbags								•	•	•	•
Anti-lock Braking System (ABS) and Electric Brake											
Distribution (EBD)	•	•	•	•	•	•	•	•	•	•	•
Vehicle Dynamic Control (VDC) with Active Brake Limited Slip (ABLS)									•	•	•
Vehicle Dynamic Control (VDC)	•	•	•	•	•	•	•				
Turn-back safety power window (driver)								•	•	•	•
Collapsible steering column	•	•	•	•	•	•	•	•	•	•	•
Front seatbelts with load limiters and pretensioners	•	•	•	•	•	•	•	•	•	•	•
Front Emergency Locking Retractor (ELR) seatbelts	•	•	•	•	•	•	•	•	•	•	•
Rear Emergency Locking Retractor (ELR) seatbelts		•	•	•	•	•	•	•	•	•	•
Child restraint anchorages (3)								•	•	•	•
					•	•	•	•	•	•	•
Child safety rear door locks		_	_	_							
Door side intrusion bars	•	•	•	•	•	•	•	•	•	•	•
Multi-reflector headlights with headlight adjustment	•	•	•	•	•	•	•	•	•	•	•
Laminated windscreen	•	•	•	•	•	•	•	•	•	•	•
Day/night rear view mirror	•	•	•	•	•	•	•	•	•	•	•
Rear window demister with timer	•	•	•	•	•	•	•	•	•	•	•
Front variable intermittent & speed sensing windscreen wipers	•	•	•	•	•	•	•	•	•	•	•
Drivers seatbelt warning lamp	•	•	•	•	•	•	•	•	•	•	•
Door ajar warning light	•	•	•	•	•	•	•	•	•	•	•
Reversing camera with predictive path technology											•
Front Protection Accessory								Opt~	Opt~	Opt~	Opt~
Exterior		I	I	I	I	I		I	I		i e
Alloy sports bar				•				•	•	•	
Black satin sports bar with integrated high mounted stop light											•
Privacy glass (2nd Row)										•	•
Front fog lights										•	•
5 channel Utili-Track system™								•	•	•	•
Tie down points				•	•	•					
Protective tub liner				•							•
Smoked bonnet protector				-							•
Side steps			•	•				•	•	•	•
	•	•					•				
Antenna			•	•	•	•		•	•	•	•
Remote keyless entry (integrated into key)	•	•	•	•	•	•	•	•	•	•	•
Front bumper body colour	•	•	•	•	•	•	•	•	•	•	•
Chrome step type rear bumper				•				•	•	•	•



NISSAN **NAVARA**

Specifications	Single Cab RX CC 4x4 Diesel	King Cab RX CC 4x4 Diesel	King Cab ST-X CC 4x4 Diesel	King Cab ST-X PU 4x4 Diesel	Dual Cab RX PU 4x2 Diesel	Dual Cab RX PU 4x4 Diesel	Dual Cab RX CC 4x4 Diesel	Dual Cab ST PU 4x2 Diesel	Dual Cab ST PU 4x4 Diesel	Dual Cab ST-X PU 4x4 Diesel	Dual Cab ST-X 550 4x4 Diesel
Remote fuel lid				•	•	•					
Front and rear mudflaps	Front	Front	Front	•	•	•	Front	•	•	•	•
Front towing hook	•	•	•	•	•	•	•	•	•	•	•
Power door mirrors	•	•	•	•	•	•	•	•	•	•	•
Power folding door mirrors with integrated indicator lights										•	•
Door mirrors	Body Coloured	Body Coloured	Body Coloured	Body Coloured	Body Coloured	Body Coloured	Body Coloured	Body Coloured	Body Coloured	Chrome	Chrome
Door handles	Black	Black	Body Coloured	Body Coloured	Black	Black	Black	Black	Black	Black	Black
Rear window guard frame					•	•					
Colours		I	I	I	I			n	n	n	n
Silver Lightning (KLO)								р	Р	Р	Р
Altitude Blue (RAK)								Р	Р	Р	Р
Flame Red (Z10)								S	S	S	S
Midnight Black (GNO)								S	S	S	S
Blue Velvet (BW9)								P	Р	Р	Р
Polar White (QM1)	S	S	S	S	S	S	S	S	S	S	S
Brilliant Silver (K23)	Р	Р	Р	Р	Р	Р	Р				
Cosmic Black (G42)		S	S	S	S	S	S				
Slate Grey (K21)	Р	Р	Р	Р	Р	Р	Р				
Titanium (KAC)		Р	Р	Р	Р	Р	Р				
Warranty	·			· ·				ı	ı	ı	
3 year / 100,000kms	•	•	•	•	•	•	•	•	•	•	•
3 year 24-Hour Roadside Assistance Program	•	•	•	•	•	•	•	•	•	•	•
MyNissan Capped Price Service*	•	•	•	•	•	•	•	•	•	•	•
Genuine Nissan Extended Warranty	Ont	Ont	Ont	Ont	Ont	Ont	Ont	Ont	Ont	Ont	Ont

- ** GVM = Gross Vehicle Mass. GVM includes the driver, passengers, full fuel tank and luggage.
- # Tare mass = unladen mass of vehicle and 10 litres of fuel, excludes tray body for Cab Chassis vehicles.
- Figures have been calculated in accordance with ADR81/02 (combined fuel consumption data). Actual fuel consumption will vary depending on driving conditions, driver behaviour, the condition of your vehicle and the accessories fitted.
- † Towing capacity is subject to towbar/towball capacity. The capacity may be reduced if a non genuine Nissan towbar is fitted. The permitted download is directly related to the laden mass of vehicle. The maximum towball download is 300kg (4WD models).
- The fitment of front protection systems and accessories having a combined weight in excess of 55 kgs will require a Positive Bonnet Restraint System & Nissan H/D front suspension springs.
- $\begin{tabular}{ll} \begin{tabular}{ll} \beg$
- Eather accented feature and upholstery may contain synthetic material.
 Applies to the first 12x10,000kms scheduled service intervals for up to 6 years/120,000kms (whichever occurs first). Some exclusions apply. Ask your Nissan Dealer or visit nissan.com.au/cpstcs for full terms and conditions.

Single and King Cab mode	ıls
Towball download	Vehicle Mass
80kg	GVM** (All variants)
100kg	Reduced loaded vehicle mass below GVM** by 30kg
150kg	Reduced loaded vehicle mass below GVM** by 110kg
200kg	Reduced loaded vehicle mass below GVM** by 185kg
250kg	Reduced loaded vehicle mass below GVM** by 250kg
300kg	Reduced loaded vehicle mass below GVM** by 310kg


4WD Dual Cab models	
Towball download	Vehicle Mass
150kg	GVM** (All variants)
200kg	Reduced loaded vehicle mass below GVM** by 60kg
250kg	Reduced loaded vehicle mass below GVM** by 130kg
300kg	Reduced loaded vehicle mass below GVM** by 200kg

	Towball download	Vehicle Mass
š	70kg	GVM** (All variants)
4501	100kg	Reduced loaded vehicle mass to below GVM** by 40kg
15UKg Reduced loaded vehicle mass to below	150kg	Reduced loaded vehicle mass to below GVM** by 110kg
200kg Reduced loaded vehicle mass to below	200kg	Reduced loaded vehicle mass to below GVM** by 180kg
	t Optional	Not available


If the loaded vehicle's rear mass is reduced as shown in the tables, the towball download can be increased correspondingly. Accordingly, if the laden mass is 180kg less than the GVM,** a towball download of 200kg is approved (2WD). Different trailer types and different trailer manufacturers have varying towball downloads. The customer will need to contact the trailer manufacturer for information as to the download. Nissan is not able to make any recommendation on the use or suitability of load-levelling or weight distribution devices to be fitted to the vehicle. Customers should contact the manufacturers of these devices for further information.



NISSAN NAVARA



Interior leather accented seat trim* (ST-X 550).



Interior cloth seat trim (ST and ST-X Dual Cab models).



Interior cloth seat trim (RX Single Cab, RX Dual Cab and RX/ST-X King Cab).









For more information please visit nissan.com.au/owners ask your Nissan Dealer or phone 1800 035 035 during normal business hours.

Follow us: @Nissan_Aus

Like us: Nissan Navara Australia

Check out: NissanAustralia Channel







All illustrations, information and specifications presented and referred to in this brochure were correct at the time this brochure was approved for printing. The colours in the photographs may vary from actual colours. However, Nissan Motor Co (Australia) Pty. Ltd. reserves the right, subject to the laws of Australia and/or the regulations of any competent authority which may apply from time to time, at its discretion at anytime and without prior notice to discontinue or change the models, features, specifications, designs and prices of the products referred to in this brochure and any optional equipment therefore without incurring any liability whatsoever to any purchaser or prospective purchaser of any such products. Some of the items referred to herein are optional at extra cost. Some options may be required in combination with other options. Always consult your Nissan Dealer for the latest information on models, specifications, features, prices, options and availability. Nissan Motor Co (Australia) Pty. Ltd. ACN 004 663 156. Updated November 2013. NAV0610